



FIBER PATCH CORD SINGLE MODE



Single Mode Patch Cord, LC typed, SC typed, Simplex and Duplex

Functions

- Data Center
- Telecommunications
- Gigabit switch equipment terminations
- High Speed Networking



Features

- Simplex & duplex
- Standard or custom lengths
- APC or UPC polish
- LSZH or PVC
- Delivered in customer-specified lengths

FEATURES

- High Temperature Stability
- Good Flexibility
- Good Durability
- Low insertion loss and back reflection loss
- Standard: Telcordia GR-326-CORE

SPECIFICATIONS

	SINGLEMODE	MULTIMODE
Insertion Loss	Typical <=0.2dB, Maximum<=0.3dB	≤0.25dB
Return Loss	≥55 dB (UPC)	
Repeatability	≤0.1	
Durability	≤0.2 dB typical change, 1000mating	
Interchangeability	≤0.2dB	
Tensile strength	>50N	
Operating Temperature	-40 to + 80°C (-40F to -176 F)	

Order Info.

Part No.	Description
FC-SM-LC-D-XX	Single Mode Fiber Patch cord, Duplex LC, XX meter (XX = length. 3m = 03, 15 = 15)

Remarks : LC, SC Simplex, Duplex, Multimode available, please contact info@cablepulse.net

